

OBJT2.E257248

Single- and Multi-layer Insulated Winding Wire - Component

[Page Bottom](#)

Single- and Multi-layer Insulated Winding Wire - Component

[See General Information for Single- and Multi-layer Insulated Winding Wire - Component](#)

RUDOLF PACK GMBH & CO. KG


E257248

AM BAEUWEG 9-11

51645 GUMMERSBACH, GERMANY

Cat. No. RUPATEX, class F for Reinforced Insulation, rated 155°C (Class F), 600 Volts peak for Information Technology, 18-38 AWG (1.00 - 0.079 mm).

Cat. No. RUPATEX, class B for Reinforced Insulation, rated 130°C (Class B), 600 Volts peak for Information Technology, 18-38 AWG (1.00 - 0.079 mm).

Marking: Company name and material designation on smallest unit container, spool or on a tag attached to the end of the wire, and the Recognized Component Mark .

[Last Updated](#) on 2008-02-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".